

# MATERIAL SAFETY DATA SHEET

Date Prepared/Revised: March 1,2004

## I. PRODUCT IDENTIFICATION

Trade Name (as labeled): SP-9800  
Manufacturer  
MURAKAMI SCREEN U.S.A.  
745 Monterey Pass Road  
Monterey Park, CA 91754  
PHONE NUMBER: 323-980-0662

## II. HARZADOUS INGREDIENTS

	CAS NO.	% RANGE	ppm
Vinyl Acetate	108-05-4	0.1 – 0.3%	<10ppm

All ingredients of this product are listed under the TSCA INVENTORY.

## III. HEALTH HAZARD INFORMATION

Threshold Limit Volume: Vinyl Acetate, 10ppm (1991-1991 ACGIH TWA)

Inhalation      A single prolonged exposure is not likely to be hazardous. Excessive exposure may cause irritation to upper respiratory tract

Skin Contact      Excessive exposure may cause minor irritation.

Eye Contact      May cause eye irritation. May cause moderate corneal injury.

## IV. FIRST AID PROCEDURES

Never give fluids or induce vomiting if patient is unconscious or having convulsions. Medical conditions aggravated by exposure may be pre-existing skin or other physical conditions.

Ingestion      Induce vomiting if large amounts are ingested. Consult with medical personnel.

Eye      Flush with flowing water immediately and continuously for at least 15 minutes. Contact a physician if irritation persists.

Skin      In case of contact, immediately flush skin with plenty of water and remove contaminated clothing and shoes. Contact a physician if irritation persists. Wash clothing before reuse. Destroy contaminated shoes.

Inhalation      None.

NOTE TO PHYSICIAN: No specific antidote. Supportive care. Treatment based on judgment of the physician in response to reactions of the patient.

## V. SPILL, LEAK, AND DISPOSAL PROCEDURES

Steps to be taken in case of spills or leaks

Spillage should be contained by, and covered with large quantities of sand, earth or similar absorbent material, then brushed in vigorously to assist absorption. The mixture can then be collected with a plastic shovel into drums or plastic bags or containers and removed for disposal. Prevent from flowing into ground or surface water.

Disposal Follow all relevant regulations for disposal. Check with your local authority.

Storing Store closed containers in a well-ventilated area. Do not store in sunlight.

*NOTE: Dispose of all wastes in accordance with federal, state and local regulations.*

## **VI. PHYSICAL PROPERTIES**

Specific Gravity at 77°F (25° C): 1.2                      Boiling Point: 100° C  
Viscosity at 77°F (25° C): 9000-13000cps              PH Value: 5.5 - 6.5  
Appearance and odor: Milky light blue liquid with slight odor

## **VII. FIRE AND EXPLOSION**

Flash Point / Method: None Flammable  
Appropriate Extinguishers: Use water spray, foam, dry chemicals and carbon dioxide.

## **VIII. REACTIVITY DATA**

Stability: Stable under the normal conditions.  
Conditions to Avoid: Heat and exposure to sunlight.

## **X. SPECIAL HANDLING PROCEDURES**

Ventilation and engineering controls: None required. Local Exhaust ventilations may be necessary for some operations.  
Respiratory protection: None required under normal use conditions. If respiratory irritation is experienced, use an approved air-purifying respirator.  
Eye Protection: Avoid any direct contact with eyes. Take a protective measurement in handlings.  
Gloves: Use vinyl or other protective gloves to prevent direct skin contact.  
Storage: Protect from freezing.

## **IX. REPORTING REQUIREMENTS AND ADDITIONAL INFORMATION**

HMIS Code System Rating=Health 1; Flammability 0; Reactivity 0.  
NFPA 704 Code System Rating=Health 0; Flammability 0; Reactivity 0.  
Volatile Organic Compound (VOC)=None.  
Contains no carcinogen or petroleum hydrocarbons.

Note: Information herein is given in good faith and to the best of our knowledge, but no warranty, expressed or implied, is made.